



W= Width, D= Depth, H=Height

230V~ 50Hz  



Termini™ 2100

DEFA Termini™ 2100 utilise a PTC heating element (PTC = Positive Temperature Coefficient). As the interior temperature rises, power output is reduced and thus power consumption as well.

The interior heater is equipped with an automatic overheating circuit breaker. This breaker is tripped at 55°C, and it is reset by disconnecting the plug and leaving the interior heater switched off until it cools down (after approx. 30 minutes). There is also a lead fuse for additional protection. If this fuse blows, the interior heater must be sent to the factory for repair.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Technical specifications

Voltage [V/Hz]	230 +/- 5%
Power [W] -25°C	2100/1300
Power [W] +25°C	1700/1060
Rated power [W]	2100
Power start, Max [W]	3300
Operating temperature [°C]	-40 /+80
W/H/D [mm]	141/49/182
Weight [gram]	750
Bracket [gram]	20
IP rating [IP]	20
Insulation class [cl]	II
Certification	EN 60335-1 and EN 50408

NOTE! Termini™ uses patented technology.

Item number

430060 (Incl. Termini™ plug for Termini™ extension cable 460860)
430061 (Incl. Schuko plug)

Delivered in 6 - pack. (Weight: 4,62Kg)
Bracket no: 418070

Part of

Termini™ 2100 (430060) is also part of ComfortKit 2100 (470060).

Usage & mounting

The interior heater is mounted in the interior of the vehicle with special holders. Termini™ can be mounted upside down under the glove compartment, on the centre console or on the A-pillar according to the enclosed mounting instruction.

Install the interior heater according to the enclosed installation guide.